CS100B: Prelim 2 Sample
October 19, 1999
7:30 PM – 9:00 PM

_____

(Print your name)

_____

(Signature)

_____

(Student ID)

Sections	10	11	12	13	14	15
(circle one)	Mon	Mon	Mon	Tue	Tue	Tue
	1:25	2:30	3:35	10:10	2:30	3:35

Instructions:

- CIRCLE YOUR SECTION! Otherwise, your test will be sent to Carpenter.
- Answer all questions by yourself! Respect academic integrity.
- Sign or initial each page.
- Show all work and comment code fragments to receive partial credit
- Use the back of each page if you need more space.
- Remember to breathe! Relax, it's only a test.

Points:

1. _____ (10 points)

2. _____ (15 points)

3. _____ (20 points)

4. _____ (25 points)

5. _____ (30 points)

Subtotal: **_____/100 points**

6. _____ (2 possible bonus points)

Total: **_____**

Problem 1 *(10 points) Short Answer questions*

Answer the following questions. Try to keep your answers concise. (Know the definitions to all the following terms to answer the 5 questions I'm not showing.) Example: Describe the client-server relationship. (Keep answers brief!)

abstraction	**`new`**
actual parameter	object
address	object oriented programming
alias	parameter
attribute	pass by reference
behavior	pass by value
call	**`private`**
class	procedural programming
class variable	**`public`**
`class`	reference
client	reference variable
constructor	return type
final	return value
flow of control	server
formal parameter	service method
garbage collection	state
identity	**`static`**
information hiding	static variable
instance variable	string
instantiation	**`String`**
interval analysis	structured programming
invoke	support method
Java	type
local variable	visibility
method	visibility modifier
method definition	**`void`**
modifier	
method invocation	

Problem 2 *(15 points) Tracing*

What is the output of the following code? Hint: Yes, this code does in fact compile and run.

```
// Class for an integer Number
class Num{
     int value;
     Num() {}
     public void add(Num number){
          number.value++;
     }
}

// Demonstrates the effects of parameter passing
class Parameter_Passing{
     public static void print(int value1, Num value2){
          System.out.println("value1= "+value1);
          System.out.println("value2= "+value2.value);
          System.out.println();
     } // method print

     public static void change1(int value1, Num value2){
          value1++;
          value2.value++;
          print(value1,value2);   // 2nd Output
     } // method change1

     public static int change2(int value1, Num value2){
          value1++;
          value2.value++;
          print(value1,value2);   // 4th Output
          return value1;
     } // method change2

     public static void main (String[] args){
          int number1=5;
          Num number2=new Num();
          number2.value=10;
          print(number1,number2); // 1st Output

          change1(number1, number2);
          print(number1,number2); // 3rd Output

          number1=change2(number1, number2);
          print(number1,number2); // 5th Output

          number2.add(number2);
          print(number1,number2); // 6th Output
     } // method main
} // class Parameter_Passing
```

Output from program:

```
value1= 5
value2= 10

value1= 6
value2= 11

value1= 5
value2= 11

value1= 6
value2= 12

value1= 6
value2= 12

value1= 6
value2= 13
```

Problem 3 *(20 points) Nested Loops*

Write a program that will generate the following tabular output for a user entered integer **n**. The main "diagonal" (the elements whose rows and columns match) must values of 1. All other elements are zero. See example output for different values of **n**.

$n = 1 \rightarrow$ 1

$n = 2 \rightarrow$ 1 0
0 1

$n = 3 \rightarrow$ 1 0 0
0 1 0
0 0 1

Your output won't have the $n = \# \rightarrow$ portion, just the table of 0s and 1s. Though not required, documenting your code will help you earn partial credit

```
public class Identity {
     public class static void main(String args[]) {

          // complete the code
          int      nn;    // size of square matrix
          int      row;   // loop index
          int      col;   // loop index

          // initialize parameters
          nn = 5;

          // print an nn x nn identity matrix

          // for each row
          for (row = 1; row <= nn; row++) {
               // print the columns (spaces) in that row
               for (col = 1; col <= nn; col++) {
                    if (row == col)
                         System.out.print ("1 ");
                    else
                         System.out.print ("0 ");
               }
               // go to the next row (line)
               System.out.print ("\n");
          }
          System.out.flush ();
     }

}
```

Problem 4 *(25 points) Complete the class!*

We're already familiar with interval arithmetic for adding two intervals. Now we wish to extend this notion to add three intervals. Using the code below as a starting point, write a method called **`addInterval`** which can be invoked on an **`Interval`** object. This method should take two **`Interval`** objects as arguments and return the sum of the two **`Interval`** objects and the **`Interval`** object that invoked the addition method.

Note: Though not required, documenting your code will earn partial credit.

```
public class Interval {

     public double minimum;
     public double maximum;

     public Interval(double min, double max) {
          minimum = min;
          maximum = max;
     }

     // complete the addition code here

     public Interval addInterval(Interval intOne, Interval intTwo) {

          // add min values
          double tempMin = minimum + intOne.minimum + intTwo.minimum;

          // add max values
          double tempMax = maximum + intOne.maximum + intTwo.maximum;

          Interval tempInterval = new Interval(tempMin, tempMax);
          return tempInterval;
     } // method addInterval

// END OF ANSWER

} // class Interval
```

Problem 5 *(30 points) Program (20 points correctness, 5 points style, 5 points documentation: all mandatory!)*

Write a program that performs interval subtraction and division between two intervals. Assume that a user enters the lower and upper bounds of both intervals. The user must also choose the operation. You should use a class that called **`Interval`** that contains all appropriate methods and variables. You do not need to employ encapsulation. Be sure to check if the user enters a zero and chooses division.

```
// PL2 problem5 sample

class Interval {
  // instance variables
  private double min;
  private double max;

  // constructors

  // default:
  Interval() {
  } // constructor Interval

  // user can set values with this constructor:
  Interval(double x, double y) {

    // check if user entered values in correct order
    if (x < y) {
      min = x;
      max = y;
    }

    // user entered values backwards, so swap:
    else {
      System.out.println("You entered your interval backwards!");
      System.out.println("Reversing interval values....");
      min = y;
      max = x;
    }

  } // constructor Interval

  // Interval subtraction
  // [al,au] - [bl,bu] = [al-bu,au-bl]
  public Interval intsub(Interval I2) {
    double I3min = min - I2.max;
    double I3max = max - I2.min;
    Interval I3 = new Interval(I3min,I3max);
    return I3;
  } // method intsub

  // Interval division
  // [al,au] / [bl,bu] = [min(al/bl,al/bu,au/bl,au/bu),
  //                      max(al/bl,al/bu,au/bl,au/bu)]
```

```
public Interval intdiv(Interval I2) {
  // check if dividing by zero (I2 contains zero)
  if (I2.min <= 0 && I2.max >= 0) {
    System.err.println("Dividing by zero not allowed, fool!");
    System.exit(0); // exit from program
  }
  // alternative check
  if (I2.min*I2.max <= 0) {
    System.err.println("Dividing by zero not allowed, fool!");
    System.exit(0); // exit from program
  }

  // otherwise, continue with division

  // all combinations to check:
  double LL,LU,UL,UU,I3min,I3max;
  LL = min/I2.min;
  LU = min/I2.max;
  UL = max/I2.min;
  UU = max/I2.max;

  // pick initial values
  I3min = I3max = LL;

  // sort out the min
  if (LU < I3min)
    I3min = LU;
  if (UL < I3min)
    I3min = UL;
  if (UU < I3min)
    I3min = UU;
  if (UU < I3min)
    I3min = UU;

  // sort out the max
  if (LU > I3max)
    I3max = LU;
  if (UL > I3max)
    I3max = UL;
  if (UU > I3max)
    I3max = UU;
  if (UU > I3max)
    I3max = UU;

  // return solution
  Interval I3 = new Interval(I3min,I3max);
  return I3;
} // method intdiv

public void intprint() {
```

```
    System.out.print("["+min+","+max+"]\n");
  } // method intprint

} // class Interval

public class interval {

  public static void main(String args[]) {

    // set up user input
    TokenReader in = new TokenReader(System.in);
    System.out.println("Welcome to wonderful world of Interval Arithmetic!");
    System.out.println();

    // enter and assign interval 1
    System.out.print("Enter interval 1 min: ");
    double I1min = in.readDouble();
    System.out.print("Enter interval 1 max: ");
    double I1max = in.readDouble();
    Interval I1 = new Interval(I1min,I1max);
    System.out.print("Interval 1: ");
    I1.intprint();
    System.out.println();

    // enter and assign interval 2
    System.out.print("Enter interval 2 min: ");
    double I2min = in.readDouble();
    System.out.print("Enter interval 2 max: ");
    double I2max = in.readDouble();
    Interval I2 = new Interval(I2min,I2max);
    System.out.print("Interval 2: ");
    I2.intprint();
    System.out.println();

    // create interval 3 to store results of I1 (op) I2
    Interval I3 = new Interval();

    // choose operation and computer result:
    System.out.print("Choose your operation [1=sub,2=div]. Choice? ");
    int choice = in.readInt();

    // subtraction
    if (choice == 1) {
      I3 = I1.intsub(I2);
      System.out.println("The result is ");
      I3.intprint();
    }

    // division
    else if (choice == 2) {
```

```
      I3 = I1.intdiv(I2);
      System.out.print("The result is ");
      I3.intprint();
      System.out.println("Thank you for you patronage. Come again!");
    }

    else
      System.out.println("Don't understand choice. Try again!");

  } // method main

} // class interval
```

Problem 6 *(2 points) Bonus problems (optional! REGRADE REQUESTS UNLIKELY TO BE ACCEPTED)*

6a) (0.5 points) What does <something> stand for (in <something>)?

6b) (0.5 points) Describe <somethings> that guarantee <something> of <something>.

6c) (0.1 points) Who <did something> to <something> to <do something>?

6d) (0.1 points) What does the expression <something> mean?

6e) (0.1 points) What is the <something> given <something> and <something>?

6f) (0.1 points) What does <something> do?

6g) (0.1 points) What does <a different something> do?

6h) (0.5 point) What is the <something> of <someone's> <something>?