

1

## CS/ENGRD 2110 FALL 2018

Lecture 3: Fields, getters and setters, constructors, testing  
<http://courses.cs.cornell.edu/cs2110>

### CS2110 Announcements

2

#### Take course S/U?

OK with us. Check with your advisor/major. To get an S, you need to do at least C- work. Do D+ work or less, you get a U.  
 HW1 due on 4 September. See Piazza note @14

Please don't email us about prelim conflicts! We'll tell you at the appropriate time how we handle them.

If you are new to the course and want to submit a quiz or assignment that is past due, talk to or email you TA and ask for an extension.

Prof's eat lunch with 7 students. Sign up on pinned Piazza note @1.5 to take part.

Quiz 1 doesn't count. Later quizzes will count.

Do a recitation in groups of 1, 2, 3 in the same recitation section. Doesn't make sense to do it with someone not in same section.

### Assignment A1

3

Write a class to maintain information about PhDs ---e.g. their advisor(s) and date of PhD. Pay attention today, you will do exactly what I do in creating and testing a class!

Objectives in brief:

- Get used to Eclipse and writing a simple Java class
- Learn conventions for Javadoc specs, formatting code (e.g. indentation), class invariants, method preconditions
- Learn about and use JUnit testing

Important: READ CAREFULLY, including Step 8, which reviews what the assignment is graded on.

Groups. You can do A1 with 1 other person. FORM YOUR GROUP EARLY! Use pinned Piazza Note @5 to search for partner!

### Homework (not to be handed in)

4

1. Course website will contain classes `Time` and `TimeTest`. The body of the one-parameter constructor is not written. Write it. The one-parameter constructor is not tested in `TimeTest`. Write a procedure to test it.
2. Visit course website, click on **Resources** and then on **Code Style Guidelines**. Study
  1. Naming conventions
  - 3.3 Class invariant
  4. Code organization
    - 4.1 Placement of field declarations
    5. Public/private access modifiers
3. Look at slides for next lecture; bring them to next lecture

### How to learn Java syntax

5

**Question on the course Piazza:**

I worked on recitation 1 in the recitation section today, but I am still confused as to when/when not to add semicolons. Is there a general rule regarding semicolon placement in java?

**Answer:** Any basic statement (one that doesn't include other statement) require ; at end, e.g.

```
assignment
return
procedure call
```

### How to learn Java syntax

6

When you have a question on syntax of statements, there are two ways to find a suitable answer:

1. Try it in Eclipse —keep trying different things until something works. HORRIBLE. You waste your time and learn nothing.
2. Look up the statement in JavaHyperText! Wonderful! Look up a statement twice and you will know it forever.

### Difference between class and object



A blueprint, design, plan  
**A class**

Can create many objects from the same plan (class). Usually, not all exactly the same.

A house built from the blueprint  
**An object**

### Overview

- An object can contain variables as well as methods. Variable in an object is called a **field**.
- Declare fields in the class definition. Generally, make fields **private** so they can't be seen from outside the class.
- May add **getter methods** (functions) and **setter methods** (procedures) to allow access to some or all fields.
- Use a new kind of method, the **constructor**, to initialize fields of a new object during evaluation of a new-expression.
- Create a **JUnit Testing Class** to save a suite of test cases, run them when necessary.

### References in JavaHyperText entries

Look at these JavaHyperText entries:

- Declaration of fields: **field**
- Getter/setter methods: **getter setter**
- Constructors: **constructor**
- Class String: **toString**
- JUnit Testing Class: **JUnit**
- Overloading method names: **overload**
- Overriding method names: **override**

### class Time

Object contains the time of day in hours and minutes.

Methods in object refer to fields in object.

Could have an array of such objects to list the times at which classes start at Cornell.

With variables **t1** and **t2** below,

t1.getHour() is 8  
t2.getHour() is 9  
t2.toString() is "09:05"

### Class Time


```

/** An instance maintains a time of day */
public class Time {
    private int hr; //hour of the day, in 0..23
    private int min; // minute of the hour, in 0..59

```

Access modifier **private**: can't see field from outside class

Software engineering principle: make fields private, unless there is a real reason to make public



### Class invariant

```

/** An instance maintains a time of day */
public class Time {
    private int hr; // hour of the day, in 0..23
    private int min; // minute of the hour, in 0..59

```

Class invariant: collection of defs of variables and constraints on them (green stuff)

Software engineering principle: Always write a clear, precise class invariant, which describes all fields.

Call of every method starts with class invariant true and should end with class invariant true.

Frequent reference to class invariant while programming can prevent mistakes.

### Getter methods (functions)

```

13
/** An instance maintains a time of day */
public class Time {
    private int hr; // hour of the day, in 0..23
    private int min; // minute of the hour, in 0..59
    /** Return hour of the day */
    public int getHour() {
        return hr;
    }
    /** Return minute of the hour */
    public int getMin() {
        return min;
    }
}
    
```

Spec goes before method. It's a Javadoc comment —starts with /\*\*

Time@fa8  
 hr 9  
 min 5  
 getHour()  
 getMin()

### A little about type (class) String

```

14
public class Time {
    private int hr; //hour of the day, in 0..23
    private int min; // minute of the hour, in 0..59
    /** Return a representation of this time, e.g. 09:05 */
    public String toString() {
        return prepend(hr) + ":" + prepend(min);
    }
    /** Return i with preceding 0, if necessary, to make two chars. */
    private String prepend(int i) {
        if (i > 9 || i < 0) return "" + i;
        return "0" + i;
    }
    ...
}
    
```

Java: double quotes for String literals  
 Java: + is String concatenation  
 Catenate with empty String to change any value to a String  
 "helper" function is private, so it can't be seen outside class

### Concatenate or catenate?

```

15
I never concatenate strings;
I just catenate those little things.
Of syllables few,
I'm a man through and through.
Shorter words? My heart joyfully sings!
    
```

### Setter methods (procedures)

```

16
/** An instance maintains a time of day */
public class Time {
    private int hr; //hour of the day, in 0..23
    private int min; // minute of the hour, in 0..59
    ...
    /** Change this object's hour to h */
    public void setHour(int h) {
        hr= h;
    }
}
    
```

No way to store value in a field! We can add a "setter method"

Time@fa8  
 hr 9  
 min 5  
 getHour()  
 getMin()  
 setHour(int)  
 toString()

setHour(int) is now in the object

### Setter methods (procedures)

```

17
/** An instance maintains a time of day */
public class Time {
    private int hr; //hour of day, in 0..23
    private int min; // minute of hour, in 0..59
    ...
    /** Change this object's hour to h */
    public void setHour(int h) {
        hr= h;
    }
}
    
```

Do not say "set field hr to h"  
 User does not know there is a field. All user knows is that Time maintains hours and minutes. Later, we show an implementation that doesn't have field h but "behavior" is the same

Time@fa8  
 hr 9  
 min 5  
 getHour()  
 getMin()  
 setHour(int)  
 toString()

### Test using a JUnit testing class

In Eclipse, use menu item File → New → JUnit Test Case to create a class that looks like this:

```

import static org.junit.Assert.*;
import org.junit.Test;

public class TimeTest {
    @Test
    public void test() {
        fail("Not yet implemented");
    }
}
    
```

Select TimeTest in Package Explorer.  
 Use menu item Run → Run.  
 Procedure test is called, and the call fail(...) causes execution to fail:

Runs: 1/1 Errors: 0 Failures: 1  
 TimeTester (Runner: JUnit 4) (0.001 s)  
 test (0.001 s)

### Test using a JUnit testing class

19

```

...
public class TimeTest {
    @Test
    public void testConstructor() {
        Time t1= new Time();
        assertEquals(0, t1.getHour());
        assertEquals(0, t1.getMin());
        assertEquals("00:00", t1.toString());
    }
}
    
```

Write and save a suite of "test cases" in TimeTest, to test that all methods in Time are correct

Store new Time object in t1.

Give green light if expected value equals computed value, red light if not:  
 assertEquals(expected value, computed value);

### Test setter method in JUnit testing class

20

```

public class TimeTest {
    ...
    @Test
    public void testSetters() {
        Time t1= new Time();
        t1.setHour(21);
        assertEquals(21, t1.getHour());
    }
}
    
```

TimeTest can have several test methods, each preceded by @Test.

All are called when menu item Run → Run is selected

Time@fa8

hr	9	Time
min	5	getHour()
		getMin()
		setHour(int)
		toString()

### Constructors —new kind of method

21

```

public class C {
    private int a;
    private int b;
    private int c;
    private int d;
    private int e;
}
    
```

C has lots of fields. Initializing an object can be a pain —assuming there are suitable setter methods

Easier way to initialize the fields, in the new-expression itself. Use:

```

C var= new C();
var.setA(2);
var.setB(20);
var.setC(35);
var.setD(-15);
var.setE(150);
    
```

C var= new C(2, 20, 35, -15, 150);

But first, must write a new method called a **constructor**

### Constructors —new kind of method

22

```

/** An object maintains a time of day */
public class Time {
    private int hr; //hour of day, 0..23
    private int min; // minute of hour, 0..59
    /** Constructor: an instance with
        h hours and m minutes.
        Precondition: h in 0..23, m in 0..59 */
    public Time(int h, int m) {
        hr=h;
        min= m;
    }
}
    
```

Purpose of constructor: Initialize fields of a new object so that its class invariant is true

Memorize!

Need precondition

No return type or void

Name of constructor is the class name

Time@fa8

hr	9	min	5	Time
				getHour()
				getMin()
				toString()
				setHour(int)
				Time(int, int)

### Revisit the new-expression

23

Syntax of new-expression: **new** <constructor-call>

Example: **new** Time(9, 5)

Evaluation of new-expression:

1. Create a new object of class, with default values in fields
2. Execute the constructor-call
3. Give as value of the expression the name of the new object

If you do not declare a constructor, Java puts in this one:

```

public <class-name> () {}
    
```

Time@fa8

hr	9	min	5	Time
				getHour()
				getMin()
				toString()
				setHour(int)
				Time(int, int)

### How to test a constructor

24

Create an object using the constructor. Then check that **all fields** are properly initialized—even those that are not given values in the constructor call

```

public class TimeTest {
    @Test
    public void testConstructor1() {
        Time t1= new Time(9, 5);
        assertEquals(9, t1.getHour());
        assertEquals(5, t1.getMin());
    }
}
    
```

Note: This also checks the getter methods! No need to check them separately.


But, main purpose: check constructor

### A second constructor

```

25
/** An object maintains a time of day */
public class Time {
    private int hr; //hour of day, 0..23
    private int min; // minute of hour, 0..59
    /** Constructor: an instance with
        m minutes.
        Precondition: m in 0..(23*60 +59) */
    public Time(int m) {
        hr= m/60; min= m%60;
        ??? What do we put here ???
    }
    ...
    new Time(9, 5)
    new Time(125)
    
```

Time is overloaded: 2 constructors! Have different parameter types. Constructor call determines which one is called



### Generate javadoc

- With project selected in Package explorer, use menu item Project -> Generate javadoc
- In Package Explorer, click on the project -> doc -> index.html
- You get a pane with an API like specification of class Time, in which javadoc comments (start with /\*\*) have been extracted!
- That is how the API specs were created.

### Method specs should not mention fields

```

27
public class Time {
    private int hr; //in 0..23
    private int min; //in 0..59
    /** return hour of day*/
    public int getHour() {
        return h;
    }
}

Time@fa8
hr 9
min 5
getHour()
getMin()
setHour(int)
toString()

public class Time {
    // min, in 0..23*60+59
    private int min;
    /** return hour of day*/
    public int getHour() {
        return min / 60;
    }
}

Time@fa8
min 545
getHour()
getMin()
toString()
setHour(int)

Decide to change implementation
Specs of methods stay the same.
Implementations, including fields, change!
    
```

### Next week's section: Exception Handling

Suppose we are supposed to read an integer from the keyboard and do something with it. If the user types something other than an integer, we want to ask the user again to type a integer.

```

String st= the integer from the keyboard;
int k= Integer.parseInt(st); // return the int that is in st
    
```

```

public static int parseInt(String s) {
    ...
    ...
}
    
```

user typed "x13", it was discovered here  
parseInt doesn't know what to do with the error

### Next week's section: Exception Handling

Read an integer from keyboard. If user types something other than an integer, ask user again to type a integer.


```

String st= the integer from the keyboard;
int k= Integer.parseInt(st); // return int that is in st
    
```

```

public static int parseInt(String s) {
    ...
    ...
}
    
```

user typed "x13", it was discovered here  
parseInt doesn't know what to do with the error (but caller does)  
So it creates and throws a NumberFormatException to the caller.  
parseInt is then terminated. It's done.



### Next week's section: Exception Handling

You must read/watch the tutorial BEFORE the recitation:

Look at the pinned Piazza note Recitation/Homework. Quiz on tutorial Monday beginning at 3PM. Bring your laptop to class, ready to solve problems (write code).

During the section, you can talk to neighbors, discuss things, answer questions together. The TA will walk around and help. The TA will give a short presentation on some issue if needed.

You will have until Friday after the recitation to submit answers on the CMS. But best to complete and submit during recitation.

Do it in groups of 1, 2, 3 people in same section. Form group on Piazza BEFORE submitting. One must invite, others must accept.